



# HD PAVER PREP

Cleaner



## Product Guide



[www.vanbeeks.com](http://www.vanbeeks.com)



## HD PAVER PREP

### UPDATE

---

**March 19<sup>th</sup>, 2024**

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Concrete interlocking pavers, slabs and retaining walls.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

### PROPERTIES

---

- Specially formulated to remove tough efflorescence
- Prepares pavers prior to sealant application
- Brightens up the colour of pavers
- Heavy duty efflorescence cleaner

### DESCRIPTION

---

Techniseal® HD Paver Prep is specially formulated to dissolve tough efflorescence (whitish salt) and remove ground-in dirt on pavers, slabs and retaining walls made of concrete. This ultra-powerful formula works deep without discolouring or damaging the surface. HD Paver Prep brightens up the colour, cleans evenly and extends the life of sealants by enabling them to better penetrate the material.

### DIRECTIONS

---

#### BEFORE YOU BEGIN

- **Do not** use on natural stone, wet-cast pavers and stamped or poured concrete.
- Wear rubber gloves and safety goggles.
- **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations
- Do not mix product with any other chemicals.
- **Never** use this product without first consulting with local authorities regarding the application of such products, waste management and run-offs.
- **Protect** people, vehicles, property, vegetation, and other surfaces not set for cleaning from product, residue, splash, fumes and wind drift.



## PREPARATION

**SURFACE WETTING:** To reduce the penetration of HD Paver Prep into sand joints and thus make product easier to rinse, first wet the surface to saturate joints with water; then let the surface dry, and apply product.

**DILUTION:** Dilution must be adjusted according to the amount of dirt and efflorescence present on the pavers. In a plastic container (like a watering can), dilute the product in water. Always pour the product in water, not the other way around. Test the dilution in a small area first.

**Recommended dilution ratio:** New pavers: 1 part product in 3 to 5 parts water. Older, never sealed pavers: 1 part product in 4 to 6 parts water. Previously sealed pavers: 1 part product in 6 to 8 parts water. It is advisable to start at a ratio of 1:8 with pavers having a very light color (ex. white or ivory) or very dark (ex. black, charcoal or granite).

Newly installed polymeric sand: Wait at least 30 days before cleaning and sealing pavers.

## APPLICATION

### Application Conditions:

- Surface must be dry, warm to the touch and free of debris.
- Temperature must be between 10 and 30°C.
- Use a consistent application method over entire surface.

**Important: Do not** apply product with a mop or a broom. **Never** let cleaning solution dry on the surface; keep it wet at all times until it is completely rinsed off. **Never** apply the product at full strength.

Clean one section of 19 m<sup>2</sup> (200 sq. ft.) at a time. On each section, starting from the bottom of the slope, cover surface with diluted solution, making sure to cover the whole section without leaving any dry spots. Next, gently scrub the surface using a street broom; **rinse immediately and thoroughly**, until all traces of foam disappear, before proceeding to another section. In cleaning each section, overlap the edges of adjoining sections to ensure that no uncleaned strips are left between them. Once all the sections have been cleaned, rinse thoroughly and let dry. If there is any efflorescence left on the surface, repeat cleaning with a weaker solution.

## CAUTION

This product may damage the material if applied at full strength; must be diluted with 4 or more parts water. never use this product without first consulting with local authorities regarding the application of such products, waste management and run-offs.

## COVERAGE

4L of concentrated product allows the cleaning of approximately 19 m<sup>2</sup> (200 sq. ft.) / 18.93L of concentrated product clean 95 m<sup>2</sup> (1000 sq. ft) when diluted 1:4 (1 part cleaner for 4 parts water). Coverage will depend on surface condition and product dilution.

## STORAGE

Store in a cool and dry place, away from the sunlight and with adequate ventilation.

## PACKAGING

Product code	Size	Units per box	Units per pallet
60200206 (241-534)	4 L	4	144
60200207 (241-536)	18.93 L	—	48

## WARNING

---

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN**

## TRANSPORT

---

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

---

Techniseal® warrants the HDPaver Prep against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice: User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m<sup>2</sup> (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m<sup>2</sup> (4 sq.ft.).