

ANTI-SLIP GRIT

For Water-Based Sealers



Product Guide



www.vanbeeks.com



SUREFOOT ANTI-SLIP GRIT FOR WATER-BASED PROTECTORS

UPDATE

December 13, 2022

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- For Techniseal® water-based Protectors.

PROPERTIES

- Easily mixes with Protector without changing its appearance
- Highly recommended for pool decks and sloped driveways

DESCRIPTION

Techniseal® Surefoot Anti-slip Grit mixes with all film-forming and water-based Techniseal® Protectors to reduce the slipperiness of sealed pavers and slabs. It provides a uniform coat and a safer, more slip resistant surface where slips and falls are likely to occur, such as pool decks, access ramps, etc.

DIRECTIONS

BEFORE YOU BEGIN

Wear adequate protective clothing. **ALWAYS TEST** on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure the results will meet your expectations.

APPLICATION

Add 5 spoons (included) of Surefoot to 1 gallon of Protector or the entire content to 5 gallons. Mix well. Do not add more than the recommended amount as it could affect the Protector's film formation. Apply the Techniseal® Protector as indicated on the product label. Stir Protector occasionally during application to maintain the additive in suspension.

CAUTION

IMPORTANT: Do not mix product with other chemicals. Use Surefoot only with a Techniseal® water-based paver Protector (EV, NS, WA).

PACKAGING

Product code	Size	Units per box	Units per pallet
60102088 (245-981)	114 g / 4 oz.	6	540

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal® warrants this Anti-Slip Grit against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 4 sq.ft. (0.4 m²) area. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²).